

Quote for AP for CA for Truck with Service Body

To tammygar@comcast.net <tammygar@comcast.net>

Tammy Garmon Shew
Senior Procurement Agent, CPP
DeKalb County
Department of Purchasing and Contracting
1300 Commerce Drive, 2nd Floor
Decatur, GA 30030
404-687-2796-ph
tgarmon@dekalbcountyga.gov

Productivity, Accountability, Customer Service, Teamwork



From: Jeff Stone <jstone@peteatlanta.com>
Sent: Wednesday, August 5, 2020 5:45 PM
To: Shew, Tammy <tgarmon@dekalbcountyga.gov>
Subject: Vehicle Summary Report.PDF

Tammy, here is your quote for the Peterbilt 337 30,000 GVW with a Altec AT41M aerial device.

Chassis List Price	\$100,280.00
Sourcewell Discount of 29.59%	\$ 29,673.00
Chassis Net Price	\$ 70,607.00
Altec Aerial Device	\$118,826.00
Total Price for Complete unit	\$189,433.00

Let me know if you need anything else. Thanks Jeff

- Vehicle Summary Report.PDF (455 KB)
- image001.png (2 KB)



Peterbilt Of Atlanta (P800)
 2395 Old 41 Highway
 Kennesaw, Georgia 30144

Dekalb County
 1300 Commerce Dr
 Decatur, Georgia 30030
 United States of America

Jeff Stone
 Cell Phone:
 Office Phone: 770-427-7281
 Email: jstone@peteatlanta.com

Robert Gordon

Vehicle Summary

Unit		Chassis	
Model:	Model 337	Fr Axle Load (lbs):	10000
Type:		Rr Axle Load (lbs):	21000
Description 1:	30000 GVW Bucket Lift	G.C.W. (lbs):	33000
Description 2:	Altec AT41M body		
Application		Road Conditions:	
Intended Serv.:	City Delivery	Class A (Highway)	100
Commodity:		Class B (Hwy/Mtn)	0
		Class C (Off-Hwy)	0
		Class D (Off-Road)	0
Body		Maximum Grade:	6
Type:	Flatbed	Wheelbase (in):	158
Length (ft):	24	Overhang (in):	45.8
Height (ft):	13.5	Fr Axle to BOC (in):	69.8
Max Laden Weight (lbs):	1000		
		Cab to Axle (in):	88.2
		Cab to EOF (in):	134
		Overall Comb. Length (in):	242
No. of Trailer Axles:	0	Special Req.	
Type:			
Length (ft):	0		
Height (ft):	0		
Kingpin Inset (in):	0		
Corner Radius (in):	0		
Restrictions			
Length (ft):	40		
Width (in):	102		
Height (ft):	13.5		

Approved by: _____

Date: _____

Note: All sales are F.O.B. designated plant of manufacture.



Sales Code	Std/Opt	Description	\$ List	Weight
Base Model				
0003371	S	Model 337 The Peterbilt Model 337 is built to take on the big jobs. That's why it's available as a Class 7 truck or tractor with a GVW up to 33,000 lbs. With a full range of suspensions and in an all-wheel-drive configuration, the 337 delivers an ideal match for applications such as wrecker, tanker, beverage delivery, municipal utilities – just about any job you can throw at it.	95,459	10,070
0091160	O	Machinery	0	0
0093340	S	City Delivery Truck or tractor which hauls freight, typically operating within a 100-mile radius, on public streets and highways and other paved surfaces. Typically includes package and freight delivery.	0	0
0095020	O	Flatbed	0	0
0098170	S	United States Registry Canadian Registry Package Requires Air Conditioning Excise Tax Canada, Speedometer to be KPH ipso MPH, Daytime Running Lights and Rubber Battery Pad in Bottom of Battery Box.	0	0
Configuration				
0200700	S	Not Applicable Secondary Manufacturer	0	0
Frame & Equipment				
0515030	S	10-5/8" Steel Rails to 285" 10.625 x 3.45 x .313 Dimension, 1,776,000 RBM; Yield Strength: 120,000 psi. Section Modulus: 14.8 cubic inches. Weight: 1.44 lbs/inch pair	0	0
0612230	O	Custom Wheelbase or Overhang Engineering approval may be required.	365	0
0644090	S	EOF Square without Crossmember End-of-frame square without crossmember. For use with body builder installed crossmember.	0	0
0651090	S	Omit Rear Mudflaps and Hangers	0	0
0651850	O	Front Mudflaps, Black, No Logo	151	22
Front Axle & Equipment				
1011830	S	Dana Spicer E1002IL 10,000 lb, 3.5 in. Drop Axle is designed for applications with a gross axle weight rating (GAWR) of 10,000 pounds. The axles have exclusive one-piece forged design knuckle including steer arm, tie rod arm and spindle. This feature helps in greater durability and reduced maintenance.	0	0
1111180	S	Taper Leaf Springs, Shocks 10,000 lb Taper leaf springs, shocks 10,000 lbs. designed for a variety of on-highway and vocational trucks. Spring designs that help reduce weight compared to multi-leaf springs.	0	0



Sales Code	Std/ Opt	Description	\$ List	Weight
1243040	S	Power Steering Sheppard HD94 Sheppard HD94 power steering gear is a light weight version of heavy duty line-haul power steering gear. For use with 12,000 to 14,000 lb. axle ratings.	0	0
1250180	O	Power Steering Reservoir Frame Mounted The power steering reservoir is a steering system that eases drivability by applying hydraulic pressure to the steering gear.	0	0
1354845	S	PHP10 Iron PreSet Hubs	0	0
1380260	S	Bendix Air Cam Front Drum Brakes 16.5x5 For use with 10,000 lbs to 14,600 lbs steer axles. Includes automatic slack adjusters & outboard mounted brake drums.	0	0
Rear Axle & Equipment				
1511430	O	Meritor RS21-160 21,000 lb Laser factory axle alignment to improve handling & reduce tire wear. Magnetic rear axle oil drain plug captures & holds any metal fragments in drive axle lube to extend service life. Parking brakes on all drive axles for optimal performance. Cognis EMGARD® FE 75W-90 synthetic axle lube provides over 1% fuel economy improvement. Reduces wear & extends maintenance intervals, resulting in increased uptime. Provides improved fluid flow to protect components in extreme cold conditions & withstand the stress from high temperatures, extending component life.	946	142
1616370	S	PHP10 Iron PreSet Hubs	0	0
1680500	S	SBM Valve Full trucks require a spring brake modulation (SBM) system for emergency braking application. This system requires an SBM valve and a relay valve with spring brakes on the rear axles. The SBM valve allows the foot valve to operate the rear axle spring brakes if a failure exists in the rear air system.	0	0
1680950	S	Stability System Not Selected Or Not Available	0	0
1681337	S	Single Drive Axle (Model 337)	0	0
1682430	S	Anti-Lock Braking System (ABS) 4S4M ABS-6. Includes air braking system.	0	0
1684200	S	Synthetic Axle Lubricant All Axles Peterbilt heavy duty models include Fuel Efficient Cognis EMGARD FE75W-90 which provides customers performance advantages over current synthetic lubricants with reduced gear wear and extended maintenance intervals, resulting in increased uptime. In addition, the lubricant provides improved fluid flow to protect gears in extreme cold conditions and withstand the stress from high temperatures, extending component life.	0	0
1687010	S	Bendix Air Cam Rear Drum Brakes 16.5x7 Bendix Air Cam Rear Drum Brakes to fit all heavy haul, construction, refuse and highway truck and tractor applications. Includes Automatic Slack Adjusters & Outboard Mounted Brake Drums.	0	0
1704890	O	Ratio 4.89 Rear Axle	0	0



Sales Code	Std/ Opt	Description	\$ List	Weight
------------	----------	-------------	---------	--------

1816140	S	Reyco 79KB Taper Leaf 21,000 lb	0	0
---------	---	---------------------------------	---	---

Engine & Equipment

2073212	O	PACCAR PX-7 250@2400 GOV@2600 660@1600	-3,550	-540
---------	---	---	--------	------

Efficiency (2017 Emissions) Includes alum flywheel housing, cruise control, and J1939 provisions (provides an interface point for the Electronic Service Analysis-ESA and other PACCAR approved diagnostic tools). Chevron Delo LE SAE 10W30 engine oil is specially formulated for new low emissions engines. Magnetic engine oil drain plug captures and holds any metal fragments in engine oil to extend service life.

- N21320 N205 120...Standard Maximum Speed Limit
- N21470 P062 NO....Cruise Control Auto Resume (
- N21480 P068 NO....Auto Engine Brake in Cruise
- N21450 P026 NO....Gear Down Protection (P026)
- N21440 P015 NO....Engine Protection Shutdown (
- N21350 P001 64....Maximum Accelerator Pedal Ve
- N21370 P059 64....Maximum Cruise Speed (P059)
- N21590 P230 YES...Enable Hot Ambient Automatic
- N21530 P233 YES...Enable Impending Shutdown Wa
- N21540 P234 60....Timer For Impending Shutdown
- N21460 P046 1400..Max PTO Speed (P046)
- N21520 P030 5.....Timer Setting (P030)
- N21570 P031 NO....Idle Shutdown Manual Overrul
- N21610 P172 40....Low Ambient Temperature Thre
- N21630 P171 80....High Ambient Temperature Thr
- N21510 P520 YES...Enable Idle Shutdown Park Br
- N21430 N201 0.....Reserve Speed Limit Offset (
- N21410 N202 0.....Maximum Cycle Distance (N202
- N21400 N203 252...Reserve Speed Function Reset
- N21420 N206 10....Maximum Active Distance (N20
- N21340 P112 120...Hard Maximum Speed Limit (P1
- N21550 P516 100...Engine Load Threshold (P516)
- N21620 P173 60....Intermediate Ambient Tempera
- N21330 N207 0.....Expiration Distance (N207)
- N21500 N209 0.....Expiration Distance (N209)

2091305	O	Engine Idle Shutdown Timer Enabled	0	0
2091315	O	Enable EIST Ambient Temp Overrule	0	0
2091372		Eff EIST NA Expiration Miles	0	0
2091640		Effective VSL Setting NA	0	0
2092016	O	Typical Operating Speed 62 MPH	0	0
2092032	O	Powertrain Optimized for Performance Best analysis for vehicles used in vocational applications or with heavy GCWRs.	0	0



Sales Code	Std/Opt	Description	\$ List	Weight
2140200	S	CARB Engine Idling Compliance PACCAR PX-7, PX-9 and MX, Cummins X15 and ISX diesel engines will include the required factory installed serialized sticker on the drivers door to identify them as meeting the NOX idling standard.	0	0
2513060	S	PACCAR 160 Amp Alternator, Brushed PACCAR 160 AMP alternator, brushed producing 160 Amps at road speed and 100 Amps at idle.	0	0
2522110	S	PACCAR 12V Starter, N/A PACCAR MX Engines PACCAR 12-volt electrical system. With centralized power distribution incorporating plug-in style relays. Circuit protection for serviceability, 12-volt light system w/circuit protection circuits number & color coded.	0	0
2538030	S	2 PACCAR Premium 12V Starting Batteries 2000 CCA Threaded stud type terminal. Stranded copper battery cables are double aught (00) or larger to reduce resistance.	0	0
2621090	S	DM Advantage ON/OFF Fan Clutch Horton DM Advantage Two-Speed Fan Clutch On/Off for heavy-duty, medium-duty and a variety of off-highway equipment.	0	0
2723210	S	18.7 CFM Air Compressor N/A X15. Furnished on engine. Teflon lined stainless steel braided compressor discharge line.	0	0
2921160	S	Spin-On Fuel/Water Separator	0	0
2921210	S	No Fluid Heat Option for Fuel Filter	0	0
2921310	S	No Electric Heat Option for Fuel Filter	0	0
3114270	S	High Efficiency Cooling System Cooling module is a combination of steel and aluminum components, with aluminum connections to maximize performance and cooling capability. Silicone radiator & heater hoses enhance value, durability, & reliability. Constant tension band clamps reduce leaks. ClimaTech extended life coolant extends maintenance intervals which reduces maintenance costs. Anti-freeze effective to -30 degrees F helps protect the engine. Low coolant level sensor warns of low coolant condition to prevent engine damage. Radiator Size by Model: 579/367 FEPTO 1325 sq in, 567/365/367: 1440 sq in, 365 FEPTO: 1184 sq in, 389/367 HH: 1669 sq in, 348: 1000 sq in, 520: 1242 sq in.	0	0
3211120	S	Radial Seal, Dry Type Air Cleaner, Frontal Air Intake. Molded rubber air intake connections with lined stainless steel clamps seal to prevent contaminants in air intake.	0	0
3365270	O	Exhaust Single RH Side of Cab DPF/SCR right-hand Under Cab.	382	29
3381770	O	Curved Tip Standpipe(s)	42	0
3387890	O	36" Ht, 5" Dia Chrome, Clear Coat Standpipe(s)	527	4
Transmission & Equipment				
4052230	O	Allison 3500 RDS-P Transmission, Gen 5 Rugged Duty Series. Includes Rear Transmission Support except on MX engines, Mobil Delvac Automatic Transmission Fluid, and Water-Oil Heat Exchange. Also includes features that monitor the transmission	10,687	195

Price Level: January 1, 2020

Deal: 30000 GVW Bucket Lift

Printed On: 8/5/2020 2:32:53 PM

Date: 3/6/2020

DTPO Number: 10017743



Sales Code	Std/Opt	Description	\$ List	Weight
		fluid, filter and clutch condition. Will display percent life remaining for the transmission fluid, filter and clutches on the shift selector. This information may be displayed using the Mode and Up and Down buttons. A wrench icon will also be included to indicate when the transmission fluid, filter or clutches need servicing. Suited for vehicles operating on/off highway and/or requiring PTO operation. Forward ratios: 1st-4.59, 2nd-2.25, 3rd-1.54, 4th-1.00, 5th-0.75, 6th-0.65. Reverse ratios: DR-(5.00).		
4210080	S	1710 HD Driveline, 1 Midship Bearing	0	0
4252890	O	Allison FuelSense 2.0 Not Desired	0	0
4252940	O	Allison Neutral At Stop Neutral at Stop features and benefits: Reduces or eliminates the load on the engine when vehicle is stopped, can help lower fuel consumption and CO2 emissions, and is included in FuelSense 2.0 Plus and Max packages only.	0	0
4256670	O	Allison 5-Speed Configuration, Wide Ratio Gears Allison 3500 transmission only.	0	0
4256920	O	Dash Mounted Push Button Shifter Available with Allison transmissions	685	0
Air & Trailer Equipment				
4510320	S	Bendix AD-IS Air Dryer, Heater Bendix Air Treatment Oil Coalescing filter, extended purge. Collects and removes solid, liquid and vapor contaminants before they enter the air brake system.	0	0
4540420	S	Nylon Chassis Hose	0	0
4543320	S	Steel Painted Air Tanks All air tanks are steel with painted finish except when Code 4543330 Polish Aluminum Air Tanks is also selected (then exposed air tanks outside the frame rails will be polished aluminum). Peterbilt will determine the optimal size and location of required air tanks. Narratives requesting a specific air tank size or location will not be accepted for factory installation. See ECAT to determine number or location of air tanks installed.	0	0
4543530	O	Clear Outside Frame of All Air System Components LH BOC	585	0
4543540	O	Clear Outside Frame of All Air System Components RH BOC	585	0
Tires & Wheels				
5069610	S	FF: BR 14ply 295/75R22.5 R268 Ecopia The R268 Ecopia is an all-position/steer radial that stands up the rigors of severe, high scrub environments in regional pickup and delivery applications. Not a tread for line haul. Diameter = 40.3 inches; SLR = 18.8 inches	0	0
5169610	S	RR: BR 14ply 295/75R22.5 R268 Ecopia R268 tread is not a Line Haul tire and is only for Pickup and Delivery or	0	0



Sales Code	Std/Opt	Description	\$ List	Weight
		Regional use. Diameter = 40.3 inches; SLR = 18.8 inches		
5190004	O	Code-rear Tire Qty 04	0	0
5211990	S	FF: Accu-Lite Steel Armor 51408PK 22.5X8.25 PHP10-2 hand holes	0	0
5311990	S	RR: Accu-Lite Steel Armor 51408PK 22.5X8.25 PHP10-2 hand holes	0	0
5390004	O	Code-rear Rim Qty 04	0	0
Fuel Tanks				
5554040	O	26" Aluminum 50 Gallon Fuel Tank LH U/C Includes steps for cab access. Paddle handle filler cap with threadless filler neck. Top draw fuel plumbing reduces chance of introducing air into the fuel system during low fuel level conditions due to the central placement of fuel pickup tube. Wire braid fuel lines increase durability & reduce potential for leaks.	5	-119
5602050	O	Location LH U/C 50 Gallon	0	0
5652890	S	DEF Tank Mounted LH BOC Models 220 and 520 mounted left hand back-of-cab.	0	0
5652990	S	Standard DEF to Fuel Ratio 2:1 Or Greater	0	0
5655019	O	DEF Tank Small	-138	0
Battery Box & Bumper				
6010800	O	Install Batteries On Temp Plywood Support BOC Includes maximum length battery cables allowable per engine manufacture requirements. Recommend three or more batteries for Class 8.	85	-97
6040550	S	Aftertreatment Aluminum Non-Slip Cab Entry Aftertreatment right-hand under cab step. DPF/SCR for diesel engines, catalyst for natural gas engines. On Models 579 specifying chassis fairings, the box is aerodynamic.	0	0
6121180	S	Steel Styled Aero Bumper Painted Cab Color Two tow points	0	0
Cab & Equipment				
6510110	S	Alum Cab 108in BBC Metton Hood w/Bright Crown Includes view window RH door and convex mirror over RH door.	0	0
6540160	O	Thermal Insulation Package in Cab Includes thick, closed-cell foam in floor, special mylar-faced foam in walls and roof structure.	19	2
6911700	S	Peterbilt UltraRide Driver Seat	0	0
6923160	S	(2) Person Passenger Seat	0	0
6939400	O	Air Ride Driver	195	0



Sales Code	Std/Opt	Description	\$ List	Weight
6939420	S	High Back Driver	0	0
6939470	S	Vinyl Driver	0	0
6939510	S	Non-Air Ride Passenger	0	0
6939540	S	Low Back Passenger	0	0
6939570	S	Vinyl Passenger	0	0
7000015	S	Adjustable Steering Column - Tilt Only	0	0
7001620	S	Steering Wheel With Peterbilt Logo Steering Wheel with embossed Peterbilt logo over horn button.	0	0
7036120	S	Interior Gray/Black Includes rugged charcoal instrument panels, glare-resistant gray dash, black bezels on gauges, (2) power ports, monochromatic molded door pads with durable in-mold color, gray molded back wall, 18 inch 4-spoke soft-touch steering wheel, soft-touch steering column cover, power lift passenger window, extruded rubber floor covering, header-mounted dome light, foot well lighting, integrated "dead pedal", (4) inside entry grab handles, (2) inside sunvisors, (2) coat hooks, (2) cup holders and map bin in dash.	0	0
7110670	O	NFPA Cab Entry Grabhandles National Fire Prevention Association compliant grabhandles featuring a larger diameter and slip resistant inserts required by many fire companies.	201	0
7210430	O	Extended Rear Window ipo Std Window-Day Cab The extended rear window protrudes two inches more than the standard conventional rear cab window. Take this into consideration when determining your loadspace.	68	18
7210540	S	Day Cab Rear Window Day cab rear window flush to back of cab.	0	0
7230060	S	1-Piece Curved Windshield	0	0
7322010	S	Combo Fresh Air Heater/Air Conditioner With radiator mounted condenser, dedicated side window defrosters, Bi-Level Heater/Defroster Controls, 54,500 BTU/HR, and silicone heater hoses.	0	0
7410040	O	Outside Sunvisor - Stainless Steel Not available with 2.1M high roof sleeper.	193	4
7560100	O	Mirrors SSTL Each Side Heated and Motorized with Switch on Door.	370	2
7560850	O	(2) Convex 8 Inch SSTL Mirrors Center mounted under mirror bracket. If rear view mirrors are heated, the convex mirrors will be heated. Option includes dual door stops.	244	4
7564110	S	Power Package Includes power door locks and power windows.	0	0
7610020	O	(1) Air Horn 15" Painted Mounted under cab.	179	8

Price Level: January 1, 2020

Deal: 30000 GVW Bucket Lift

Printed On: 8/5/2020 2:32:53 PM

Date: 3/6/2020

DTPO Number: 10017743



Sales Code	Std/ Opt	Description	\$ List	Weight
7725710	O	Standard Speaker Package For Cab (2) Speakers	117	4
7725725	O	ConcertClass w/CD, Bluetooth Phone and Audio Includes AM/FM, WB, USB and MP3.	414	10
7748140	O	CB Terminals/Wiring Mounted Under Header	45	0
7748300	O	(1) 48" CB Antenna	63	1
7748500	O	CB Antenna Mounting, LH Mirror Available with Rami only on 1.9m, available without Rami on medium duty	47	1
7850210	O	Plug-In Auto Reset Circuit Breaker in place of fuses in junction box.	40	0
7851480	S	Peterbilt Electric Windshield Wipers With Intermittent Feature.	0	0
7900090	O	Triangle Reflector Kit, Ship Loose Florescent triangle emergency road flares are designed to meet and exceed all DOT standards.	17	13
7900270	O	Fire Extinguisher, Cab Mounted Hazmat approved UL listed/rated ABC	54	8
7901130	O	Backup Alarm (107 DB)	53	3
8021380	S	Air Restriction Indicator Mounted on air cleaner, intake piping, or firewall	0	0
8071870	S	Main Instrumentation Panel, Graphics Display Includes speedometer with trip odometer, tachometer with hourmeter and outside air temperature display, voltmeter, engine oil pressure, engine coolant temperature, fuel level, primary and secondary air pressure gauges. Includes standard warning light package: high water temperature, low oil pressure, and low air pressure warning lights with audible alarms, high beam, turn signal, low fuel, parking brake, and ice warning indicators; seat belt reminder; rocker switches with long-life LED indicators; multi-function turn stalk with flash-to-pass feature (night mode flashes headlights and marker lights; day mode flashes headlights only), intermittent windshield wiper and headlamp beam control. Hydraulic braked trucks do not include air pressure gauges.	0	0
8111110	S	Headlights Composite Fender Mounted Integral park, turn, and side marker	0	0
8120980	S	(5) Marker Lights, Aero LED	0	0
8140120	S	Incandescent Square Stop/Turn/Tail/Backup Left-hand / right-hand square end of frame or dropped a-brace	0	0
Paint				
8500710	O	Standard Paint Color Selection	-200	0
8530770	S	(1) Color Axalta Two Stage - Cab/Hood Base Coat/Clear Coat	0	0

Shipping Destination



Sales Code	Std/ Opt	Description	\$ List	Weight
8999990	O	Shipping Destination Other Than Dealer (Specify by narrative)	0	0

Options Not Subject To Discount

9400091	S	Peterbilt Class 7 Standard Coverage 1 year/Unlimited Miles/km	0	0
9400093	O	PACCAR PX-7 Standard Coverage 3 years/Unlimited Miles/Unlimited hrs	0	0

Miscellaneous

9409800	S	2017 EPA Emissions Engine Warranty Only	0	0
9409869	O	Presentation Created With SmartSpec	0	0

Promotions**Order Comments**



Total List Price (W/O Freight & Warranty & Surcharges)	\$108,935	
Marketing and Service Support Fee		\$475
Prepaid Freight		\$2,450
Total Surcharge/Options Not Subject To Discount		\$0
Total Weight		9,795

Prices and Specifications Subject to Change Without Notice.

Unpublished options may require review/approval.
Dimensional and performance data for unpublished options may vary from that displayed in CRM.

PRICING DISCLAIMER

While we make every effort to maintain the web site to preserve pricing accuracy, prices are subject to change without notice. Although the information in this price list is presented in good faith and believed to be correct at the time of printing, we make no representations or warranties as to the completeness or accuracy of this information. We reserve the right to change, delete or otherwise modify the pricing information which is represented herein without any prior notice. We carefully check pricing specifications, but occasionally errors can occur, therefor we reserve the right to change such prices without notice. We disclaim all liability for any errors or omissions in the materials. In no event will we be responsible for any damages of any nature whatsoever from the reliance upon information from these materials. Please check your order prebills to confirm your pricing information